

# **HYDROX BIO 68**

Environment friendly HYDROX BIO 68 is a Readily Biodegradable sterntube lubricant, non-toxic to marine life, with the same performance and cost saving benefits as HYDROX 550.

## Environmental credentials of **HYDROX BIO 68**

- · Produced from renewable sources.
- Biodegradability according to OECD: OECD-301B = 92.5%.
- · Non toxic to the marine environment
- Independently tested and found to be non-toxic to the following organisms:









# Sterntube equipment compatibility

- · Approved by major seal manufacturers.
- Approved for use with RAILKO sterntube bearings: Sternsafe™ & CY160LS.
- Widely used in vessels fitted with white metal bearings.
- Suitable for use in different vessel types with various seal arrangements including Cruise ships, Tankers, Ferries, Car Carriers and Dredgers.

### **HYDROX BIO68**

#### Main applications

- Sterntube lubrication
- Lubrication of some stabiliser models

### Viscosity @ 40°C

70cSt (approx.)

#### Viscosity Classifications

ISO 68 SAE 30

#### Density @ 15°C

0.92 (approx.)

#### Pour Point (IP15)

#### Anti-corrosion (SKF salt water Emcor Test)

Passes

### **HYDROX BIO 100**

HYDROX BIO 100 (ISO viscosity grade 100) is also available and provides the same lubrication, performance and environmental benefits as HYDROX BIO 68.

